

1/14

[FIG. 1]







DOCKET NO.: 8048-1179
INVENTOR: Takeshi KODA et al
Filing DATE: August 25, 2006
TITLE: INFORMATION RECORDING DEIVCE AND METHOD, AND COMPUTER PROGRAM


3/14

[FIG. 3]


Sector number of start position of border zone	3FF00h~B25FFh	(middle)	165700h~ (outer)
First	1792 ECC	2368 ECC	2944 ECC
border zone	56MBytes	74MB	92MB
	384ECC	480 ECC	608 ECC
border zone	12MB	15MB	19MB

4/14


[FIG. 4]





[FIG.5]




6/14









[FIG. 9]




10/14


[FIG. 10]








[FIG. 12]





PALL EX UUA [FIG. 14] 😘 🚬 Data area Blank disc L1 L0 Start data additional recording \$102-5 L1 LO \$102-3 S102-4 About 0.1 mm About 0.25mm Border close process 104s-1-105c-1 <u>√S1</u>15-2 - S112 L1 SMA BÖ SMA LI L0 S115-1 1045-0 About 0.25mm Finalize process About 0.1mm 0.5mm or more 105c-1 0.5mm or more About 0.25mm 104-1 104s-1

S117-2

+,S117-1

104-0

104s-0

About 0.25mm 0.5mm or more

S118

LO.

LI

BO

L1

L0